

CATÁLOGO Válvulas





411



413

ANGLE HOSE VALVES for use with hose storage devices and hydrants. Has a 300 lb rating. UL listed and FM approved. Cast brass.

P/N	DESCRIPTION
411	1 1/2" NPT(F) x 1 1/2" NPT(F) Valve
B411	1 1/2" NPT(F) x 1 1/2" NPT(F) Valve, Domestic
412	2 1/2" NPT(F) x 2 1/2" NPT(F) Valve
413	1 1/2" NPT(F) x 1 1/2" NST(M) Valve
B413	1 1/2" NPT(F) x 1 1/2" NST(M) Valve, Domestic
414	2 1/2" NPT(F) x 2 1/2" NST(M) Valve
B414	2 1/2" NPT(F) x 2 1/2" NST(M) Valve, Domestic
415	1 1/2" NPT(F) x 1 1/2" NPSH(M) Valve



421



423

PRESSURE REDUCING ANGLE VALVES can be adjusted to restrict pressures up to 175 lbs. Locking pin device restricts full opening of valve by untrained personnel. Pin may be removed by fire personnel for unrestricted operation. UL listed. Cast brass.

P/N	DESCRIPTION
421	1 1/2" NPT(F) x 1 1/2" NPT(F) Valve
422	2 1/2" NPT(F) x 2 1/2" NPT(F) Valve
423	1 1/2" NPT(F) x 1 1/2" NST(M) Valve
424	2 1/2" NPT(F) x 2 1/2" NST(M) Valve



433



B433

GATE VALVES for use on standpipes, fire pumps or hydrants. Straightway pattern, with a 300 lb rating. UL listed and FM approved. Cast brass.

P/N	DESCRIPTION
433	2 1/2" NPT(F) x 2 1/2" NST(M) Gate Valve w/ Cap and Chain, Non-Rising Stem
B433	2 1/2" NPT(F) x 2 1/2" NST(M) Gate Valve w/ Cap and Chain, Non-Rising Stem, Domestic
434	3" NPT(F) x 2 1/2" NST(M) Gate Valve w/ Cap and Chain, Rising Stem



443



B443

SINGLE HYDRANT GATE VALVES for use on standpipes, fire pumps or hydrants. Straightway pattern, with a 300 lb rating. UL listed and FM approved. Cast brass.

P/N	DESCRIPTION
443	2 1/2" NST(F) x 2 1/2" NST(M) Single Hydrant Gate Valve w/ Swivel, Non-Rising Stem
B443	2 1/2" NST(F) x 2 1/2" NST(M) Single Hydrant Gate Valve w/ Swivel, Non-Rising Stem, Domestic